MX Series

ENGLISH TRADITION

Professional top-class products with a powerful and economic engine, this series is the perfect tool for an intensive use. Compact, efficient and reliable, it combines endurance and functionality.



Main applications:

- Construction
- Road works
- Industrial applications





OPTIONAL:
MTS - MANUAL TRANSFER SWITCH 40A
(FOR MANUAL CONTROL VERSIONS 230V)



OPTIONAL: TRANSPORTATION KIT WITH HEIGHT-ADJUSTABLE FOLDING HANDLES



PROTECTIVE CARTER MADE OF SHEET STEEL



LARGE AUTONOMY THROUGH THE INTEGRATED PLASTIC FUEL TANK OF 24 LITERS



CONTROL PANEL COMPLETE

GENERATING SET	MX 12000	MX 12000
MAIN DATA	SINGLE PHASE	THREE PHASE
POWER RATING - THREE PHASE	kVA / kWe	kVA / kWe
STAND BY POWER-LTP		13,9 / 11,1
CONTINUOUS POWER - COP	-	11,8 / 9,5
POWER RATING - SINGLE PHASE	kVA / kWe	kVA / kWe
STAND BY POWER-LTP	11,9 / 10,7	5,6/5,0
CONTINUOUS POWER - COP	10,0 / 9,1	5,0/4,5
VOLTAGE (Volt)	230	400/230
FREGUENCY (Hz)	50	50
POWER FACTOR (cos Ф)	9,0	0,8 / 0,9
ENGINE		
BRAND	Honda	Honda
MODEL	GX630	GX630
FUEL	Petrol	Petrol
CYLINDERS / DISPLACEMENT (cc)	2 V angle / 688	2 V angle / 688
COOLING SYSTEM	Air	Air
STARTING SYSTEM	Electric	Electric
SPEED (rpm)	3000	3000
CONSUMPTION		
FUEL CONSUMPTION at 75% of load (L/h)	4,23	4,16
FUEL TANK CAPACITY (L)	24	24
RUNNING TIME at 75% of load (h)	5,67	5,12
OVERALL DIMENSIONS		
LENGTH (mm)	960	960
WIDTH (mm)	638	638
HEIGHT (mm)	665	665
DRY WEIGHT (Kg)	147	151
STANDARD EQUIPMENT		
DIGITAL DISPLAY	V-Hz-h	V - Hz- h
TANK (Type)	Plastic	Plastic
SOCKETS	3 x 230V SCHUKO 16A IP54	3 x 230V SCHUKO 16A IP54
	1 x 230V CEE 16A IP44	1 x 230V CEE 16A IP44
	1 x 230V CEE 32A IP44	1 x 400V CEE 16A IP44
PROTECTIONS		
OIL GUARD	Standard	Standard
MAGNETO THERMAL PROTECTION	Standard	Standard
THERMAL PROTECTION	Standard	Standard
ALTERNATOR PROTECTION (IP)	23	23
OPTIONALS		
MTS-MANUAL TRANSFER SWITCH	0	0
TRANSPORTATION KIT With fixed handles	0	0
TRANSPORTATION KIT With folding handles	0	0
o = Accessory available		

o = Accessory available



www.masonsgenerators.com

MASONS DISTRIBUTOR IN YOUR AREA IS: